

GRAPH/NET Computer Integrated Design System

Fault Dictionary

The Key to the Diagnostic Display

Copyright (C) 1983, 1984, 1985
Graphic Horizons, Inc.
60 State Street
Boston, MA 02109
617-396-0075

GRAPH/NET Fault Dictionary

This document is not to be reproduced in any form or transmitted in whole or in part, without the prior written authorization of Graphic Horizons, Inc.

The information in this document is subject to change without notice and should not be construed as a commitment by Graphic Horizons, Inc. The Company assumes no responsibility for any errors that may appear in this document.

Graphic Horizons, Inc. will make every effort to keep users apprised of all documentation changes as quickly as possible. The Reader's Comments card is distributed with this document to request users' critical evaluation to assist us in preparing future documentation.

Computer Integrated Design is a copyright of Graphic Horizons, Inc.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
000	Boot never got going, StackReset doesn't work or other major problem in the processor board (or clock).
001	Simple Branches fail.
002	Main Data Path Failure.
003	Dual Address failure on Registers.
004	Y Ram Failure.
005	Const/Carry Propogate failure.
006	ALU failure.
007	Conditional Branch failure.
008	Looping failure.
009	Control Store (or Write Control Store) failure.
010	Hung in Disk Boot.
011	Memory Data Error.
012	Memory Address Error.
013	Disk never became ready.
014	Couldn't boot from either disks.
015 - 020	Bad Interrupts Reading Floppy Disk Data.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
030	VFY Hung.
050	Bad Error Message from VFY.
051	Empty stack bit not working.
052	Could not load TOS.
053	Push did not work.
054	Stack Empty did not go off.
055	Data error in push.
056	Empty or Full set when that is not the case.
057	Data error in bit 15 of the stack.
058	Stack empty set when the stack is full.
059	Data error on stack.
060	Data error after POP. Bit 14.
061	Data error after POP. Bit 13.
062	Data error after POP. Bit 12.
063	Data error after POP. Bit 11.
064	Data error after POP. Bit 10.
065	Data error after POP. Bit 9.
066	Data error after POP. Bit 8.
067	Data error after POP. Bit 7.
068	Data error after POP. Bit 6.
069	Data error after POP. Bit 5.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
070	Data error after POP. Bit 4.
071	Data error after POP. Bit 3.
072	Data error after POP. Bit 2.
073	Empty wrong.
074	Data error after POP. Bit 1.
075	Data error after POP. Bit 0.
076	Empty not set after all pops.
077	Call test failed.
078	Odd didn't jump on a 1.
079	Odd jumped on a 0.
080	Byte sign didn't jump on 200.
081	Byte sign jumped on 0.
082	C19 didn't jump when it should have.
083	BCPI31 didn't jump when it should have.
084	C19 jumped when it shouldn't have.
085	BCPI31 jumped when it shouldn't have.
086	GTR didn't jump.
087	GTR jumped when it shouldn't have.
088	GEQ didn't jump.
089	GEQ jumped when it shouldn't have.
090	LSS didn't jump when it should have.
091	LSS jumped when it shouldn't have.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
092	LEQ didn't jump.
093	LEQ jumped when it shouldn't have.
094	GEQ didn't jump on equal.
095	LEQ didn't jump on equal.
096	Carry didn't jump when it should have.
097	Carry jumped when it shouldn't have.
098	Overflow didn't jump when it should have.
099	Overflow jumped when it shouldn't have.
100	And-Not ALU function failed.
101	Or ALU function failed.
102	Or-Not ALU function failed.
103	And ALU function failed.
104	Or-Not ALU function failed.
105	Not-A ALU function failed.
106	Not-B ALU function failed.
107	Xor ALU function failed.
108	Xnor ALU function failed.
109	OldCarry-Add ALU function failed.
110	OldCarry-Sub ALU function failed.
111	OldCarry-Add /w No OldCarry failed.
112	Fetch error on Force Bad Parity.
113	Unexpected Parity error.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
114	No parity errors on force bad parity.
115	Wrong address on force bad parity.
116	Upper 4 bit test failed.
117	MDX test failed.
118	Stack upper bits test failed.
119	Store/Fetch test failed.
120	Unexpected refill.
121	BPC test failed.
122	Fetch4 test failed.
123	Fetch4R test failed.
124	Store4 test failed.
125	Fetch2 test failed.
126	Store2 test failed.
127	NextOp test failed.
128	Fetch/Store overlap failed.
129	Bad interrupt Loc 4.
130	Bad interrupt Loc 14.
131	Bad interrupt Loc 20.
132	Bad interrupt Loc 30.
133	Data error on memory sweep.
134	Address error on memory sweep.
135	Field didn't work.
136	Dispatch did not jump.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
137	Wrong Dispatch target.
138	Data error on inverted memory sweep.
139	Address error on inverted memory sweep.
150	Sysb not loaded correctly or hung.
151	Sysb did not complete.
152	Illegal Boot Key.
153	Hard Disk Restore Failure.
154	No such boot.
155	No interpreter for that key.
156	Interpreter file is empty.
157	Disk Error.
158	Floppy error.
159	Malformed Boot File.
160	Checksum error in microcode.
161	Checksum error in QCode.
162 - 168	Bad interrupts.
169	Not used
170	No ACK from keyboard; on PERQ2 workstations only
171	Wrong disk type for this Sysb; on PERQ2 workstations only
198	QCode interpreter microcode not entered correctly.
199	System not entered - calls or assignments don't work.
200	System entered, InitMemory to be called.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
201	InitMemory entered.
203	SAT and SIT pointers set.
204	StackSegment number set.
205	Reading the BootBlock.
206	System version number set.
207	Head of free-segment-number list set.
208	First system segment number set.
209	System boot disk set.
210	System boot character set.
211	Boot block read.
212	Default heap segment number set.
213	First used segment number set.
214	Before setting freelists of data segments.
215	Before trying to allocate a segment number.
216	Temporary segment number allocated.
217	Ready to enter loop to find memory size.
218	Exited from memory size loop.
219	Restored mangled word.
220	Released temporary segment number.
221	Boot file has wrong size.
222	Modified the location of I/O segment.
223	Adjusted free memory.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
224	Freelists of data segments set.
225	Set screen segment.
226	Header buffer allocated for swapping.
227	Status buffer allocated for swapping.
228	SwappingAllowed set false.
229	All boot-loaded segments set UnSwappable (if booted from floppy), InitMemory complete, ready to return to System.
230	Starting to increase number of segments allowed (because memory is larger than 1/4 megabyte).
231	Changed maximum of SITSeg.
232	Changed size of SITSeg.
233	Changed maximum of SATSeg.
234	Changed size of SATSeg.
235	Created new unallocated segment numbers.
236	Finished InitMemory.
300	InitIO to be called.
301	InitIO entered.
310	Device Table allocated, calling InitDeviceTable
311	InitDeviceTable entered.
312	Allocating the hard disk control block.
313	Allocating the EIO Disk Control Block.
314	Allocating the pointer's control block.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
315	Allocating the timer's control block.
316	Calling Video - Setup Device Table.
331	Video setup device table entered.
332	Screen control blocks and display lists allocated.
333	Video device table setup complete.
350	InitTablet complete, InitCursor to be called.
358	Configuration module initialization to be called.
360	StartIO to microcode complete, allocating Z80 messages.
370	Messages allocated, calling Vid_Initialize.
371	Vid_Initialize entered, calling InitTablet.
372	InitTablet complete, calling InitCursor.
373	InitCursor complete, enabling video interrupts.
380	Vid_Initialize complete, calling Key_Initialize.
381	Key_Initialize entered, allocating status buffer.
382	Status buffer allocated, allocating circular buffers.
383	Circular buffer allocated, enabling keyboard interrupts.
390	Key_Initialize complete, calling Dsk_Initialize.
391	Dsk_initialize entered.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
392	Disk interrupts enabled, allocating temporary buffers.
393	Buffers allocated, calling LocateDskHeads.
394	LocateDskHeads entered, about to search for track zero.
395	Track zero located.
396	LocateDskHeads complete, calling FindSize.
397	FindSize entered, about to seek to a 24MByte sector.
398	Disk Size determined.
399	FindSize complete, disposing temporary buffers.
400	Dsk_Initialize complete, calling Flp_Initialize.
401	Flp_Initialize entered, allocating Floppy status buffer.
402	Status buffer allocated, allocating Floppy, control block.
403	Floppy control block allocated, initializing variables.
404	Variables initialized, enabling Floppy interrupts.
410	Flp_Initialize complete, calling GPB_Initialize.
411	GPB_Initialize entered.
412	Allocating the GPIBs High Volume Buffer.
413	Allocating the GPIBs Status Buffer.
414	Allocating the GPIBs circular buffer.
415	Enablne GPIB interrupts.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
416	Sensing to see if the GPIB is there.
420-427	Talking to the GPIB.
430	GPB_Initialize complete, calling RS2_Initialize.
431	RS2_Initialize entered.
432	Allocating an RS232 high volume buffer.
433	Allocating an RS232 circular buffer.
434	Allocating an RS232 status buffer.
435	Enabling RS@#@ interrupts.
436	Allocating temporary buffers.
437	Sensing to see if the RS232 is there.
438	Disposing of temporary buffers.
440	RS232 devices initialization complete.
441	Ptr-initialize entered.
442	Allocating the pointer's status buffer.
443	Enabling pointer interrupts.
444	Sensing to see if the pointer is there.
445	Turning on the pointer.
446	Determining if the pointer is connected.
447	Turning off the pointer.
450	Ptr_Initialize complete, calling Clk_Initialize.
451	Clk_Initialize entered.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
452	Allocating the clock's status buffer.
453	Buffer allocated, enabling Clock interrupts.
454	Allocating temporary buffers.
455	Sensing to see if the clock is there.
456	Disposing of temporary buffers.
460	Clk_Initialize complete, calling Z80_Initialize.
461	Z80_Initialize entered.
462	Allocating the Z80's high volume buffer.
463	Allocating the Z80's status buffer.
464	Enabling the Z80.
465	Allocating temporary buffers.
466	Sensing to see if the Z80 is there.
467	Disposing of temporary buffers.
470	Z80 device initialization complete.
499	About to exit InitIO.
500	InitIO complete, InitStream to be called.
600	InitStream complete, FSInit to be called.
700	FSInit complete.
800	Command file and Console opened, InitExceptions to be called.

GRAPH/NET Fault Dictionary

<u>Display</u>	<u>Description</u>
810	InitExceptions complete.
820	System version number set.
822	Current 60 Hz. clock value read.
824	60 Hz time reference set, TimeStamp time reference to be set.
900	FSSetUpSystem to be called.
950	FSSetUpSystem complete.
951	About to enable swapping (if booted from hard disk).
952	FSLocalLookup and EnableSwapping complete.
960	Calling Ethernet initialization.
961	EIOInit entered.
962	Ethernet device table initialization complete.
963	EtherSeg created.
964	Buffers allocated from EtherSeg.
965	EtherSeg made unmoveable.
966	Exiting EIOInit.
969	Ethernet initialization complete.
970	Loading Z80 from ZBoot file.
979	Z80 load complete.
980	Loading double precision microcode files.
999	System fully initialized, system title line to be printed.