

Performance,  
manageability,  
and investment  
protection

Compaq  
Evo Thin  
Client T30



**COMPAQ**

Inspiration Technology

[compaq.com](http://compaq.com)

# Compaq Evo Thin Client T30

<b>Processor</b>	333 MHz Geode GX1 integrated processor from National Semiconductor
<b>Memory</b>	16, 128 MB FLASH 32, 256 MB DRAM
<b>Protocol</b>	Integrated Microsoft RDP and Citrix ICA 6 protocols.
<b>Display Support</b>	VESA Monitor Support, scaleable video up to 1280 x 1024, 16-bit color, up to 85-Hz refresh rate
<b>Audio</b>	Output - 1/8-inch mini, full 16-bit stereo, 44-KHz sample rate    Input - 1/8-inch mini microphone
<b>Input/Output/Peripheral</b>	Keyboard - Compaq Enhanced USB with Windows keys (104 keys) included; Mouse - Compaq USB mouse included Printer - Local and/or network printers on ICA (virtual port redirection ready); Video - VGA-type video output (DB-15)
<b>Options Supported</b>	Generic text printer, WL 110 and WL 215 CPQ wireless, Microtouch Touch Screen (TFT5005) Scroll mouse as default mouse (auqlified for 128/256 configuration)
<b>Networking</b>	TCP/IP with DNS and DHCP; 10/100BaseT Fast Ethernet, twisted pair (RJ-45); Point-to-Point Protocol (PPP); Multiple master browser support on ICA; Supports Citrix load balancing on ICA; SNMP support allows configuration of terminal settings, reporting terminal configuration and attached devices, traps; DHCP support for automatic firmware upgrades and unit configuration
<b>Communications</b>	Serial, parallel, PS/2, USB, PCMCIA; ICA Remote dial-up via external modem (only with Windows CE.net)
<b>Communication Protocols</b>	RDP and ICA 6
<b>Terminal Personalities Supported</b>	Emulations for IBM, DEC, Tandem, Wyse, SCO, and others
<b>Resident Operating System</b>	Microsoft Windows XP Embedded and Windows CE.net (Available 2Q02)
<b>Server OS Compatibility/Support</b>	Microsoft Windows NT Server 4.0, Terminal Server Edition; Microsoft Windows 2000; Citrix MetaFrame
<b>Centralized Management</b>	Rapport™ Administrative Software for Compaq Thin Clients
<b>Physical Characteristics</b>	Height/Width at Base/Depth 260 mm (10.2 in)/117.5 mm (4.6 in)/216 mm (8.5 in);
<b>Dimensions are approximate.</b>	Shipping Weight - 3.5 kg (7.7 lbs)
<b>Environmental</b>	Temperature range on/off -0° to +40°C (32° to 104°F) / -40° to +60°C (-40° to 140°F) (Fanless design); Humidity (on-off) - 10 to 90%/10 to 95% noncondensing; Power - Worldwide 100-240 VAC, 50-60 Hz; Energy saving automatic power-down
<b>Regulatory Compliance</b>	Ergonomics German ZH1/618; EN29241-3, approved; EPA Energy Star Safety UL 1950, CSA 950; TUV-GS (EN60 950) approved RF Interference FCC Class B; CE Mark; EN50022B, VCCI
<b>Warranty</b>	3 Years parts and Labor. Certain restrictions apply. Consult the Compaq Customer Support Center for details.

©2002 Compaq Computer Corporation

Compaq Information Technologies Group, L.P. Compaq, the Compaq logo and Evo are trademarks of Compaq Information Technologies Group, L.P. in the U.S. and/or other countries.

Microsoft and Windows are trademarks of Microsoft Corporation in the U.S. and/or other countries. All other product names mentioned herein may be trademarks of their respective companies. Compaq shall not be liable for technical or editorial errors or omissions contained herein.

16CB-0302A-WWEN