

VMware® VMmark™ V1.1 Results		
Vendor and Hardware Platform: HP ProLiant DL585G5 Virtualization Platform: VMware ESX 3.5 Update 3 (build 123630)	VMmark V1.1 Score = 20.43 @ 14 Tiles	
Tested By: Hewlett Packard	Test Date: 1/12/2009	
Performance Section Performance	Configuration Section Configuration	Notes Section Notes for Workload

Performance

	webserver		javaserver		mailserver		fileserver		database		
TILE_0	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1818.90	1.79	18123.30	1.09	1861.58	1.70	18.66	1.45	1984.88	1.33	1.45
p1	1798.45	1.77	18130.80	1.09	1763.60	1.61	18.27	1.42	1972.55	1.32	1.42
p2	1788.17	1.75	18127.53	1.09	1736.88	1.58	18.16	1.42	1959.90	1.31	1.41
TILE_1	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1873.75	1.84	18119.90	1.09	1784.17	1.63	18.35	1.43	2281.40	1.53	1.48
p1	1857.72	1.82	18123.10	1.09	1874.15	1.71	18.28	1.42	2284.32	1.53	1.49
p2	1846.38	1.81	18118.38	1.09	1863.35	1.70	17.80	1.39	2277.68	1.53	1.48
TILE_2	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1908.47	1.87	18134.10	1.09	1712.10	1.56	18.76	1.46	2220.30	1.49	1.47
p1	1886.72	1.85	18144.03	1.09	1639.78	1.50	18.70	1.46	2211.07	1.48	1.46
p2	1878.28	1.84	17676.90	1.06	1768.03	1.61	18.48	1.44	2211.20	1.48	1.46
TILE_3	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1838.00	1.80	18136.03	1.09	1744.62	1.59	18.21	1.42	2264.47	1.52	1.46

p1	1814.88	1.78	18166.55	1.09	1852.38	1.69	18.14	1.41	2272.30	1.52	1.48
p2	1796.83	1.76	18154.12	1.09	1902.50	1.73	17.92	1.40	2272.78	1.52	1.48
TILE_4	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1869.20	1.83	18158.47	1.09	1628.25	1.48	19.25	1.50	2292.72	1.54	1.47
p1	1853.33	1.82	18150.20	1.09	1698.50	1.55	19.18	1.49	2297.22	1.54	1.48
p2	1836.38	1.80	18135.05	1.09	1711.45	1.56	19.02	1.48	2294.03	1.54	1.48
TILE_5	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1932.25	1.90	18088.78	1.09	1648.05	1.50	19.31	1.50	2223.60	1.49	1.47
p1	1919.65	1.88	18101.40	1.09	1776.70	1.62	19.04	1.48	2229.78	1.49	1.49
p2	1905.58	1.87	18092.00	1.09	1831.67	1.67	19.05	1.48	2220.10	1.49	1.50
TILE_6	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1843.10	1.81	18122.88	1.09	1630.05	1.49	18.85	1.47	2230.28	1.49	1.45
p1	1833.90	1.80	18108.67	1.09	1802.38	1.64	18.36	1.43	2234.53	1.50	1.47
p2	1822.50	1.79	18130.72	1.09	1811.83	1.65	18.12	1.41	2236.07	1.50	1.47
TILE_7	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1840.10	1.81	18159.65	1.09	1579.62	1.44	18.74	1.46	2258.53	1.51	1.44
p1	1807.45	1.77	18149.47	1.09	1684.08	1.54	18.43	1.44	2266.12	1.52	1.45
p2	1797.30	1.76	18158.40	1.09	1570.67	1.43	18.28	1.42	2271.05	1.52	1.43
TILE_8	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1911.90	1.88	18145.78	1.09	1520.08	1.39	19.46	1.52	2285.20	1.53	1.46
p1	1898.60	1.86	18145.60	1.09	1770.03	1.61	19.22	1.50	2283.25	1.53	1.50
p2	1896.03	1.86	18155.97	1.09	1738.33	1.58	19.22	1.50	2281.85	1.53	1.49
TILE_9	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1871.03	1.84	18158.92	1.09	1532.55	1.40	18.45	1.44	2208.53	1.48	1.43
p1	1849.70	1.82	18153.00	1.09	1709.78	1.56	18.32	1.43	2195.53	1.47	1.45

p2	1830.70	1.80	18143.38	1.09	1781.90	1.62	18.10	1.41	2191.53	1.47	1.46
TILE_10	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1905.03	1.87	18205.42	1.10	1418.12	1.29	19.51	1.52	2246.05	1.51	1.43
p1	1877.75	1.84	18172.88	1.09	1619.15	1.48	19.43	1.51	2239.55	1.50	1.47
p2	1874.00	1.84	18170.08	1.09	1765.28	1.61	19.39	1.51	2236.97	1.50	1.49
TILE_11	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1872.70	1.84	18154.20	1.09	1342.05	1.22	19.42	1.51	2211.00	1.48	1.41
p1	1857.83	1.82	18153.75	1.09	1604.28	1.46	19.17	1.49	2190.82	1.47	1.45
p2	1842.78	1.81	18154.75	1.09	1654.05	1.51	19.12	1.49	2188.53	1.47	1.45
TILE_12	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1863.97	1.83	18124.03	1.09	1282.38	1.17	18.94	1.48	1840.88	1.23	1.34
p1	1850.38	1.82	18111.90	1.09	1578.25	1.44	18.77	1.46	1824.05	1.22	1.38
p2	1839.75	1.81	18117.88	1.09	1647.45	1.50	18.33	1.43	1794.05	1.20	1.38
TILE_13	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1872.67	1.84	18133.72	1.09	1283.90	1.17	19.01	1.48	2257.70	1.51	1.39
p1	1852.50	1.82	18123.20	1.09	1530.80	1.40	18.74	1.46	2264.53	1.52	1.44
p2	1826.22	1.79	18119.10	1.09	1607.62	1.47	18.55	1.45	2269.07	1.52	1.44
p0_score:	20.17										
p1_score:	20.43										
p2_score:	20.43										
Unreviewed_VMmark_Score:	20.43										

Configuration

Server and Network

Server Manufacturer and Model	HP ProLiant DL585G5
Processor Vendor and Model	Quad-Core AMD Opteron 8386 SE
Processor Speed (GHz)	2.8GHz
Number of Sockets/Cores per Socket	4 Sockets / 4 Cores per Socket (16 Cores Total)
Primary Cache	128KB I + 128KB D on chip per core
Secondary Cache	2MB
Other Cache	6MB
Memory	128GB (16 x 8GB PC2-5300 667MHz Registered ECC DDR2 DIMMs)
Disk Subsystem Type	Direct attach SAS for operating system, FC SAN for VMs
Number of Disk Controllers	1 SMART Array P800 (O/S)
Number of Host Bus Adapters	2
Host Bus Adapter Vendors and Models	2 QLogic QLE2460 fibre channel HBAs
Number of Network Controllers	4
Network Controller Vendors and Models	1 x embedded dual-port HP NC371i Gigabit adapter, 3 x dual-port HP NC380T Gigabit adapters
Network Switch Vendors and Models	HP ProCurve 2900
Network Speed	1000BaseT
Other Hardware	None
Other Software	None
Hardware Availability Date	April 26, 2009
Software Availability Date	November 2008
Virtualization Software	
Vendor, Product, Version, and Build	VMware ESX 3.5 Update 3, build 123630
Virtualization Type	Hardware Virtualization
Supplemental Software	None

Virtualization Software Availability Date	November 2008
Storage	
Array Vendor, Model, and Firmware Version	HP StorageWorks MSA 2000, Storage Controller Firmware J200P16, Management Controller Firmware W420R30
Fibre Channel Switch Vendors and Models	HP StorageWorks SAN Switch 4/32
Disk Space Used	1268.33 GB for VMs
Array Cache Size	1 GB
Number and Size of LUNs	9 LUNs, 1.6TB per LUN
RAID Type	RAID 0
Number of Members per RAID Set	12 drives per RAID set
Disk Vendor, Model, and Speed	HP Dual Port 146GB SAS 15K RPM
Clients	
Number of Clients	14
System Model(s)	HP ProLiant DL360G5
Processor Vendor(s) and Model(s)	Intel Xeon
Processor Speed(s) (GHz)	2.83GHz
Number of Sockets/Cores per Socket	1 Sockets / 4 Cores per Socket (4 Cores Total)
Memory	2GB
Network Controller Vendor and Model	HP NC373i Gigabit Adapter
Operating System, Version, and Service Pack	Microsoft Windows Server 2003 Enterprise Edition, Service Pack 2
Other Hardware	None
Other Software	None

Notes for Workload

Server and Network Notes

- | Server BIOS settings:
 - | Power Regulator: Static High Performance (default Dynamic Power Savings Mode)
 - | Ultra Low Power State: disabled (default enabled)
 - | Memory Channel Mode: Independent Mode (default Combined Mode)
 - | AMD Virtualization Technology: enabled (default disabled)

- | QLogic HBA BIOS settings:
 - | Fibre Channel tape support disabled (default enabled)
 - | Data rate option set to 3 (default 2)
 - | Execution Throttle set to 128 (default 16)

- | vSwitch Configuration:
 - | vSwitch0 for the Service Console configured on vmnic0
 - | vSwitch1 for all webserver VMs configured on vmnic1, vmnic2, vmnic3 & vmnic4
 - | vSwitch2 for all VMs excluding webserver configured with 120 ports (default 56) on vmnic5, vmnic6 & vmnic7

- | Storage Configuration:
 - | storage0 configured to store odd-numbered database VMs
 - | storage1 configured to store even numbered database VMs
 - | storage2 configured to store all VMs other than database for tiles 0 & 1
 - | storage3 configured to store all VMs other than database for tiles 2 & 3
 - | storage4 configured to store all VMs other than database for tiles 4 & 5
 - | storage5 configured to store all VMs other than database for tiles 6 & 7
 - | storage6 configured to store all VMs other than database for tiles 8 & 9
 - | storage7 configured to store all VMs other than database for tiles 10 & 11
 - | storage8 configured to store all VMs other than database for tiles 12 & 13

Virtualization Software Notes

- | vmfs2 was unloaded prior to run
- | pegasus CIMOM server was unloaded prior to run
- | virtualized MMU was enabled for all VMs (default Automatic)

- | ethernet adapter type set to Enhanced vmxnet for all VMs
- | logging was disabled for all VMs
- | IDE & floppy devices were removed on all VMs except for fileserver VM's (default enabled)
- | syncTime set to TRUE for all VMs except for Mailserver11
- | Misc.RunningVCpuLimit set to 192 (default 128)
- | ql2maxqdepth=64
- | BufferCache.SoftMaxDirty=85 (default 15)
- | IRQ.RoutingPolicy = 0 (default 2)
- | COW.MaxHeapSizeMB = 64 (default 32)
- | Disk.SchedNumReqOutstanding = 128 (default 32)
- | VMFS3.MaxHeapSizeMB = 64 (default 16)

Operating System Notes

- | Microsoft Windows Server 2003 virtual machines were updated to Service Pack 2, as well as KB933360
- | Javasever Microsoft Windows Server 2003 VMs were also updated with KB958644
- | Fileserver and Webserver VMs were updated to SLES 10 SP2

Software Notes

None.

Client Notes

- | Microsoft Windows Server 2003 client machines were updated to Service Pack 2
- | TCP TOE chimney was disabled on all clients (default enabled)

Other Notes

None

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit www.vmware.com/products/vmmark.

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark™ is a product of [VMware, Inc.](#). VMmark utilizes SPECjbb®2005 and SPECweb®2005, which are available from the [Standard Performance Evaluation Corporation \(SPEC®\)](#).