



HP Cluster Configuration Support Matrix
For Microsoft Windows Server 2003, EE & HP StorageWorks MA8000/EMA12000/EMA16000

Config	Supported Servers*	Server Software	Host Bus Adapters (HBAs)**	Multi Path Software	Storage Information	Interconnects (Switches)	Other
#1 Windows Server 2003, EE	Max supported nodes = 2 DELL <ul style="list-style-type: none"> • PowerEdge 1650 • PowerEdge 1750 • PowerEdge 2650 • PowerEdge 6650 * Note: Servers can be used homogeneously or heterogeneously within a cluster.	DELL OpenManage Server Assistant 7.3.3 & Systems Mgmt 3.3.3	FCA2404 Driver: 5-4.82.a16 FW: 1.01a2 BIOS: 1.63a1 ** Note: HBAs must be used homogeneously within a cluster.	Secure Path Ver: 4.0c Raidisk.sys ver: 3.7.2.240	StorageWorks MA8000/EMA12000 (HSG80) Storage Controller Software FW: 8.7-3 SW: v8.7+	HP 2GB SAN Switches 8/16 ports FW: 3.1.1 <ul style="list-style-type: none"> • SAN Switch 2/8 EL • SAN Switch 2/16 EL • SAN Switch 2/16 	March 2004