

E7805A - PDU Power Cord with an L6-30P Plug

Technical Data

Product Number E7805A

Connect a modular PDU to a power source.

The E7805A power cord is used to connect any 100-240V, 16 amp modular Power Distribution Unit (PDU) to a UPS power source.

This cord cannot be used with the E7675A (100-127V) PDU.

Features

- 200-240VAC
- 16 amp maximum
- Length: 4.5m (177.2in)
- Plug: L6-30P

What you get in the box

■ 1 power cord

Plug Nomenclature Explained

L6-30P

- L = Locking
- **6** = Maximum voltage rating (6 represents 200-240VAC)
- **30** = Maximum amperage rating (plug only)*
- $\mathbf{P} = \text{Plug}$

Installation

Plug the C19 connector end into the C20 inlet of the PDU and the L6-30P plug into the UPS. Twist the L6-30P plug to lock into the UPS.

Tools required for installation:

 Phillips #1 screwdriver (only needed if using the PDU retaining clamp to secure the cord to the PDU.)

Certifications

• Meets UL and CSA requirements.

Related Products

A shorter version of this PDU power cord is available:

- E7799A 2.5m (98.4in)
- * The maximum electrical rating for the complete power cord is 16 amps. This rating is determined by the combined ratings of all the power cord components (plug, cable and connector).

E7805A power cord ends



Modular PDU C20 Inlet



C19 Connector



L6-30P