



## Chenbro A9671

[www.chenbro.com.tw/](http://www.chenbro.com.tw/)

### Product Information

**Model#: A9671**

**Size (LxWxH in/mm): 22.8x14.6x26.8in/583x370x680mm**

**5.25" Bays: 12**

**3.50" Bays: 1 exposed, 8 internal**

**Fans: 4 x 9cm (12 x 9 cm, 2 x 8 cm, 1 x 6 cm optional)**

**Power Supply: Dual or Trio Redundant PSU**

**3 x PS/2 standard PSU**

**Other Information: SCA HDD Raid module is optional**

**Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.**

### Additional Information

**Associated Model #s: A9641, A9651, A9661, A9651-7, A9661-7, A9671, A9681, A9691**

**Options: Hot Swap Drives.  
Redundant PSU**

**Chassis Configuration (as tested with Intel's L440GX+ server board)**

**Model tested: A9671**

**Fans (qty x size): 5 x 92 mm, 1 x 60 mm**

**Hard drives: 3 - Seagate\* ST39102LW Cheetah\***

**Processor: 2 - 450Mhz Pentium® II processor**

**Memory: 512MB SDRAM**

**Power Supply: EMAC\* RPD-5300F-RVS2**

**Additional Information:**

\* Third party names and brands are the property of their respective owners.

**Note: Modifications to the tested configuration may cause variations in actual performance.**

### List of Intel

#### Real Server Boxed Boards

**Mechanical Validation**

**L440GX+, N440BX, T440BX**

**Thermal Validation**

**L440GX+, N440BX, T440BX, R440L**

**EMI (CISPR) Validation**

**N440BX, T440BX**