

Shin-G GS-2000

www.shin-g.com.tw



Product Information

GS-2000

Height (in/mm): 16.1 x 27.9 x 25.8in/410 X 710 x 655mm

Slots: 23

Slots: 0

Dimensions: 12cm, 8 x 9cm

Power Supply: EMAC RPD-5300F-RV/300W redundant

Information: Base configuration is without power supply. Power Supply is available upon request.

The above information is provided by the chassis manufacturer. It is the sole responsibility of the manufacturer. Intel assumes no liability for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #: None

Options: Hot Swap Drives

Redundant Power- 400W

Chassis Configuration (as tested with Intel's L440G board)

Model tested: GS-2000

Fans (size, qty): 90mm, 10

Hard drives: 3-Seagate* ST39102LW Cheetah*

Processor: 2 x 450MHz Pentium® II

Memory: 256 MB

Power Supply: EMAC RPD-5300F-RV2

Additional Information: none

* Third Party names and brands are the property of the respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanical Validation

L440GX+

Thermal Validation

L440GX+

EMI (CISPR) Validation